SHELLAC

Sun Down

Created by CND™ Education Ambassador Samantha Birkett-Leigh





CND™ SUPPLIES

- CND™ SHELLAC™ Base Coat
- CND™ SHELLAC™ Gel Polish Colors:
 - Chance Taker
 - Mover & Shaker
 - Safety Pin
 - Salmon Run
- CND™ SHELLAC™ NoWipe Top Coat
- CND™ LED Lamp

ART SUPPLIES

- Striping brush
- Gold chrome
- Sponge applicator
- Retention+ clear powder

INSTRUCTIONS

- 1. P.E.P. the natural nail. (For details see our CND™ SHELLAC™ Application & Removal Step-by-Step.)
- Apply a thin layer of CND™ SHELLAC™ Base Coat*. Cure for 10 seconds in the CND™ LED Lamp, using pre-set button 1.
- 3. Apply CND™ SHELLAC™ Safety Pin to the top half of the nail and lock for 10 seconds, using pre-set button 1
- **4.** Apply **CND™ SHELLAC™** Mover & Shaker diagonally to the bottom right third of the nail and lock for 10 seconds, using pre-set button 1.
- 5. Apply CND™ SHELLAC™ Salmon Run diagonally to the left side of the nail. Cure for 1 minute in the CND™ LED Lamp, using pre-set button 2S.
- 6. Apply CND™ SHELLAC™ No Wipe+ top coat. Cure

- for 1 minute in the CND™ LED Lamp, using pre-sei button 3.
- Apply gold chrome to the Safety Pin portion of the nail.
- **8.** Apply CND™ SHELLAC™ No Wipe+ top coat. Cure for 1 minute in the CND™ LED Lamp, using pre-set button 3.
- 9. Using a striping brush, paint the sun design with CND™ SHELLAC™ Chance Taker, DO NOT CURE.
- 10. Sprinkle with CND™ Retention+ Clear powder. Cure for 1 minute in the CND™ LED Lamp, using pre-set button 2S
- 11. Remove the residue of powder, using a lint-free pacifightly saturated with 99% IPA.

^{*} Choose CND™ SHELLAC™ Base Coat / Wear Extender depending on the condition of the client's nail

^{**} Choose CND™ SHELLAC™ Original / Duraforce / Xpress5 Top Coat depending on the desired level of protection, based on clients needs